

Product Data Sheet



Induro Mix&Fill Binder

Code	Description
2MF/104	Induro Mix&Fill Binder

Technical Data	A Cellulose based binding medium for mixing with sanding dusts to produce fast drying fillers for use in nail holes, splits/shakes and gaps between joints upto 5mm in width/depth.
Properties	Fillers prepared with this binder are easy to apply, fast drying and are easily sanded. Overcoatable with oils, water and solvent based flooring finishes.
Mixing Guidelines	1 part of the binding medium should be mixed with 1 – 2 parts of clean sanding dust from 80 – 120 grit sanding to produce a paste with a smooth consistency.
Application Guidelines	Preparation: - The flooring should be clean, dry and sanded back to bare timber. Application: - The filler should be applied over the whole area using a trowel, scraper or other straight edged tool. Ensure that holes, shakes and gaps are completely filled. - Allow to dry, typically 20 – 60 minutes, depending amount applied and the ambient conditions. When dry, sand with 100 -120 grit. - Repeat the application process if required. Using this product outside these guidelines can lead to immediate and latent problems with the integrity of the finish.
Important Information	➤ Failure to give the filler adequate drying can result in film defects and shrinkage after the lacquering process. ➤ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation. ➤ Product should be stored above 5°C and protected from frost. ➤ Finished products should not be subjected to environments with temperatures of < 2°C. ➤ Out of scope with 2004/42/EC.
Health & Safety	Reference should be made to the appropriate MSDS for this product, which can be found at www.morrells.co.uk The use of appropriate personal protection equipment (PPE) is recommended. This product is intended for professional use only.



The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN
Tel: +44 (0)161 406 5300 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk
Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT: Reg No GB 712 5048 66



PM 10591
MORRELLS WOODFINISHES LTD
REGISTERED TO
BS EN ISO 9001:2000