



BOSTIK 3070

CORK PERIMETER SEALANT

TECHNICAL SHEET NO: TDS02265 24/02/2025

SMART ADVANTAGES

- Quick drying
- Can be sanded
- Excellent thermal and acoustic insulation

DESCRIPTION

Bostik 3070 is perfect for filling expansion joints up to 5mm wide between various types of flooring, such as ceramic, parquet, and laminate boards. This cork expansion gap filler is designed to prevent cracks and deformations caused by temperature and humidity changes. Without proper expansion joints, floors can develop unsightly cracks over time.

Additionally, Bostik 3070 is suitable for sound and thermal insulation in applications like window frames to masonry, door frames, partition walls, and other areas requiring effective insulation

Measurement results for a joint dimension of 1950 x 10 x 110 mm (extract from the Fraunhofer Institute's test report)

Formation of the joint	R ST, W (extended joint insulation dimension)
Empty joint	19dB
Filled with mineral fibre	37dB
Filled with BOSTIK 3070	46dB
Filled with BOSTIK 3070 spray cork and approx. 3 mm permanent elastic joint sealant on one side (after 3 weeks vulcanization time)	49dB
Maximum insulation of the test arrangement	50dB



TECHNICAL CHARACTERISTICS

Colour	Natural cork
Form	Visco-plastic
Specific gravity	0.35g/cm ³
Composition	Cork granulate and solvent free binder
Thermal resistance	-30 °C to +120 °C
Application temperature	+5 °C to +35 °C
Drying times	Approximately 6-12 hours

COVERAGE

For a lateral joint size of 5x5mm, approx. 12 linear metres

APPLICATION

IMPORTANT: Before using Bostik 3070, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

All phases of the application should comply with the current editions of:

- BS 8102 Code of practice for protection of below ground structures against water ingress.
- BS 5325 Code of practice for installation of textile floor coverings.
- BS 8203 Code of practice for installation of resilient floor coverings.
- BS 8201 Code of practice for installation of flooring of wood and wood-based panels.

Ensure the correct PPE is worn during use.

APPLICATION

- Before applying Bostik 3070 ensure the surface is clean and dry.
- Use painter's tape to protect surrounding areas and to ensure a precise application.
- For consistency, a liquid cork gun can be used to apply the product.
- Once Bostik 3070 has been applied, use a putty knife or spatula to remove any excess and to smooth out the surface.
- A cork floor sealant can be used to protect Bostik 3070, ensuring that the joint remains clean.
- Once applied, leave Bostik 3070 24 -48 hours before returning the area to use.

CLEANING

- Clean tools and equipment with warm, soapy water immediately after use. Dried and hardened material can only be removed mechanically.

STORAGE

- Store and transport securely. Store for up to 12 months from date of manufacture in original, unopened packaging, clear of the ground, in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from excessive drafts, frost, damp, condensation and dew.

PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik 3070, available at www.bostik.com/uk.

PACKAGING

Product codes	30110970	500ml sausage x 30
----------------------	----------	--------------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone:	01785 272625
Sales:	customer.service@bostik.com
Technical advice:	technical.service@bostik.com
Safety data sheets:	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.